FEATURES

POWER TRAIN	YES	NO	OFFERED
· Engine 59 Rated HP 4-Cylinder liquid cooled Diesel, 2.2L (135 cu in) Direct Injection, Turbocharged and Intercooled, Electronic Engine Control 45.6 PTO HP @ 2500 RPM – Shuttle Emission Standard Category: Tier 4			
· Dual Element Dry Type Air Cleanser			
· Transmission 12Fx12R Power Shuttle with 4 Synchronized Gears and 3 Ranges			
· Sealed Wet Disc Brakes			
· Pedal Operated Differential Lock			
· PTO: Rear – 540 RPM Independent Electro Hydraulic			
HYDROLIC SYSTEM			
· 3-point Hitch Cat. II with Position Control Standard			
· Lift Capacity @ 24 inches – 3,307 lb. (1500 kg)			
· Telescopic Stabilizers			
· Telescopic Draft Link Ends			
· Dual Engine Driven Gear Pumps			
· Flow at Remotes 12.8 GPM (48.6 LPM)			
· Hydrostatic Power Steering			
· One Rear Remote Valve Standard on Cab Models, up to 3 Possible. Loader Joystick Standard			

INTRUMENTS

- Combination Digital and Analog Front Dash Display
- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam Indicator, Engine Oil Pressure, PTO Engagement, Battery Charge (alt) Indicator, Glow Plug Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control

OTHER STNDARD FEATURES

- ISO Mounter Flat Platform w/ Molded Rubber Floor Mat
- One Piece Tilt-Up Hood
- 3 Position Tilt Steering
- Deluxe Adjustable Suspension Seat with Arm Rest
- 2 Post Folding ROPS and Retractable Seat Belt
- Turn Signals, Flashers, Tail Lights and SMV Emblem
- 4 Headlights

CAB FEATURES

- Heating and Air Conditioning
- Wired for Radio and Speakers
- Front and Rear Wiper / Washer
- 2 Front Work Lights
- 2 Rear Work Lights
- Rear and Side Opening Windows
- Right and Left Entry Doors

YES	NO	OFFERED

	YES	NO	OFFERED
· Right and Left External Windows			
· Deluxe Digital Display with Ground Speed, Engine Coolant, Temperature, Fuel Level and Diagnostic Readout			
· ROPS Certified			
· Recirculation Filter			
· **Note: 3-Point Backhoe Installation Voids Warranty**			

IMPLEMENT FEATURES

LOADER

	YES	NO	OFFERED
· One Piece Main Frame with Tapered Arms and Single Cross Member			
· Quick Attach Loader Frame Mount with Pin Lock			
· Built-in Parking Stands			
· (2) 2.75 inch Double Acting Lift Cylinders			
· (2) 2.75 inch Double Acting Bucket Cylinders			
· Hydraulic Lines Routed Inside Main Frame for Protection and Visibility			
· 3rd Function Capable, Soft-Drive Capable			
· Galvanized Steel Bushings with Recessed Grease Points			
· Universal Skid Steer Implement Attachment			
· Grille Guard Standard			
· Maximum Lift Height: 110.2 Inches at Pivot			
· Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 1760 lbs.			
· Breakout Force: 2870 lbs.			
· Rated Hydraulic Pressure: 2277 PSI			